

# Hydraulic Bottle Jacks



## PORTABLE HYDRAULIC POWER IN A RUGGED, RELIABLE UNIT

Choose from this complete line of premium-quality, standard bottle jacks. Ideal for use in any number of industrial lifting and pushing applications.

**Beveled BASE** The 9015B, 9022B and 9030B feature a beveled base which allows the jack to “follow” the load, reducing the chance of dangerous side-loading.

Many jacks feature screw extensions and all can be used in the vertical, angled or horizontal positions.

Serrated or contoured saddles help stabilize the load for a safer lift.

All jacks meet ANSI B30.1 standards and carry the Power Team Marathon Lifetime Warranty.



*110 ton jack features dual pumps for time-saving two-speed operation*



# Low Profile Bottle Jacks

## THE RIGHT CHOICE FOR THOSE LOWER CLEARANCE JOBS.

All the quality, features and lifting capacity of the standard jacks in short form. The 12-ton and 20-ton models feature screw extensions for added versatility.

All jacks meet ANSI B30.1 standards and carry the Power Team Marathon Lifetime Warranty.



### 1 Horizontal Applications

All jacks operate both vertically and horizontally for use in a variety of lifting, pushing and spreading applications.

### 2 Low Profile

With such a low retracted height, you'll be able to work in the most confined spaces.





## ORDERING INFORMATION

See current price list for shipping weights.

Cap. Tons	Stroke in. (mm)	ORDER NUMBER	Retracted Height Min. in. (mm)	Length of Screw Ext. in. (mm)	Height with Screw Ext. in. (mm)	No. Pump Strokes to Ext. piston 1in. (25mm)	Saddle Dia. in. (mm)	Base Size in. (mm) Beveled Base: †	Pump Handle Length in. (mm)	Handle Effort at Rated cap. lbs. (kg)	Carry Handle	Product Weight lbs. (kg)
2	4 1/2 (114)	9002A	7 1/8 (181)	1 15/16 (49)	13 3/16 (344)	5	1 (25)	4 11/32 x 2 9/16 (110x65)	12 1/4 (311)	75 (34)	No	4.8 (2.2)
3	4 1/2 (114)	9003A	7 1/2 (191)	2 3/8 (60)	14 3/8 (365)	10	1 1/8 (29)	4 1/2 x 2 27/32 (114x72)	19 1/4 (489)	45 (20.4)	No	5.8 (2.6)
5	4 3/4 (121)	9005A	7 7/8 (200)	2 3/4 (70)	15 5/8 (391)	12	1 3/8 (35)	5 3/16 x 3 (132x76)	21 7/16 (545)	55 (24.9)	No	8 (3.6)
8	4 3/4 (121)	9008A	7 7/8 (200)	2 3/4 (70)	15 5/8 (391)	18	1 1/2 (38)	6 x 3 1/2 (152x89)	23 13/16 (605)	75 (34)	No	12.1 (5.5)
12	5 7/8 (149)	9112A	9 1/2 (241)	3 1/8 (79)	18 1/2 (470)	26	1 7/8 (48)	6 1/2 x 4 3/16 (165x106)	23 13/16 (605)	60 (27.2)	Yes	17.5 (7.9)
<b>NEW</b> 15	6 1/8 (156)	9015B	9 1/16 (230)	4 5/16 (110)	19 1/2 (495)	27	2 3/8 (60)	5 1/8 x 5 1/2 (130x140) †	27 9/16 (700)	90 (40.8)	No	18.3 (8.3)
20	6 1/4 (159)	9120A	10 5/8 (270)	1 9/16 (40)	16 7/8 (429)	22	2 (51)	7 3/16 x 5 1/16 (183x129)	31 1/2 (800)	70 (31.7)	Yes	28.5 (12.9)
<b>NEW</b> 22	6 1/8 (156)	9022B	9 7/16 (240)	4 5/16 (110)	19 7/8 (505)	36	2 3/8 (60)	6 1/2 x 6 5/16 (165x160) †	27 9/16 (700)	90 (40.8)	Yes	23.6 (10.7)
30	6 1/4 (159)	9030A	11 (279)	-----	17 1/4 (438)	35	2 3/8 (60)	7 9/16 x 5 9/16 (192x141)	39 3/8 (1000)	50 (22.7)	Yes	41.2 (18.7)
<b>NEW</b> 33	5 5/8 (143)	9033B	9 7/16 (240)	3 15/16 (100)	19 (483)	56	2 9/16 (65)	7 1/4 x 6 15/16 (184x176) †	27 9/16 (700)	88 (39.9)	No	32 (14.5)
50	6 3/4 (171)	9050A	12 (305)	-----	18 3/4 (476)	35	3 (76)	9 5/16 x 7 3/8 (237x187)	39 3/8 (1000)	85 (38.6)	Yes	78 (35.4)
<b>NEW</b> 110	6 1/8 (156)	9110B	11 13/16 (300)	-----	17 15/16 (456)	40/160 ‡	4 3/8 (111)	13 3/8 x 11 7/16 (339x291) †	27 9/16 (700)	79 (35.8)	Yes	154.3 (70)

‡ 2 Speed: Rapid advance ≈ 40 strokes; Lift mode ≈ 160 strokes

### Low Profile Bottle Jacks:

12	3 3/4 (95)	9012A	6 3/4 (171)	3 (76)	13 1/2 (343)	26	1 7/8 (48)	6 1/2 x 4 3/16 (165x106)	23 13/16 (605)	60 (27.2)	Yes	14 (6.4)
20	3 3/8 (86)	9020A	7 1/8 (181)	1 9/16 (40)	12 (305)	22	2 (51)	7 3/16 x 5 1/16 (183x129)	31 1/2 (800)	70 (31.8)	Yes	22.2 (10.1)
30	3 1/8 (79)	9130A	7 1/8 (181)	-----	10 1/4 (260)	35	2 3/8 (60)	7 9/16 x 5 9/16 (192x141)	39 3/8 (1000)	50 (22.7)	Yes	30.2 (13.7)